

Technical Data Sheet

2 Port Professional USB 2.0 to Serial Converter FT2232D Chip with RX and TX Status LED

Model Number: GM-FTDI2X-LED

Rev 03.210315



2 Port USB to Serial adapter with RX/TX LED Indicators easily adds 2 standard serial ports to your desktop, laptop or other mobile device and fully supports Windows 10.

- RXD, TXD Status LED Array
- Easy Plug and Play installation
- USB interface: standard Type A female
- Baud rates up to 921.600bps

Features

- RXD, TXD Status LED Array
- Easy Plug and Play installation
- Baud rates up to 921.6kbps
- Dual 16 Byte hardware data buffer (up/down stream)
- Cable Length: 3 feet

Product Information

- Model Number: GM-FTDI2X-LED
- Packing List:
 -

Specifications

OVERVIEW

Product Type	
Electrical Protections	15KV ESD Protection
Mountable	
Material	
Compliance	N/A
LED indicators	Power, TX/RX
Requires Host to Function	

0

Serial Modes	RS232
RS232 Signals	DCD, RxD, TxD, DTR, GND, DSR, RTS, CTS, RI
RS422 Signals	
RS485 2-wire Signals	
RS485 4-wire Signals	

SERIAL SPECS

Maximum Data Rate	921.6 Kbps
Minimum Data Rate	300 baud/bps
Data Bits	
Parity	
Stop Bits	
Flow Control	
FIFO	

Specifications Cont.**ENVIRONMENTAL**

Operating Temperature	-40C ~ 85C
Operating Humidity	5% to 95% RH
Storage Temperature	-40C ~ 85C

PHYSICAL

Length	inches
Width	inches
Height	inches
Item Weight	lbs
Ship Weight	0.3875 lbs

OS SUPPORT

Supported Operating Systems	Linux, OSX 10, Windows 10, Windows 8, Windows 7
-----------------------------	---

WARRANTY

Warranty Period	
-----------------	--

PRODUCT URL

GM-FTDI2X-LED Product Page	
----------------------------	--