

Technical Data Sheet Rev 06-240719

USB 3.0 4 Port Industrial Din Rail Mount Hub w/Power Adapter

Model Number: GM-HU34-PS



Features

- Includes Mounting brackets and DinRail Clip for mounting options
- Supports UASP function (with Windows 8 native USB 3.0 Host driver only)
- Redundant 9VDC to 24VDC power input
- Over-current detection and protection circuit design
- Compliant with Universal Serial Bus 3.0 Specification

Package Contents

- 3-Pin Terminal Block
- DIN rail bracket
- Hub
- Mounting Bracket
- Power Cable
- Screw Pack
- USB Cable

Specifications

OVERVIEW

Model No	GM-HU34-PS
Product Type	USB Hub
Compliance	None or N/A
UPC	045079158474
Country of Origin	China
LED indicators	Power
Chipset	VL811-Q8P
Electrical Protections	15KV

PHYSICAL

Ship Weight (lbs)	1.57 lbs
Ship Weight (kg)	0.71 kg
Material	Steel
Color	Black
Mountable	Din-Rail Mount Surface Mount Wall Mount

Specifications Cont.

CONNECTIONS	
USB Specification	USB 3.2 Gen 1
Upstream Port Type	USB 3.2G1 / 3.0 Type-B Female
Maximum Data Rate	5 Gbps
Downstream Port Count	4
Downstream Port Type	4x Type A USB 3.2 G1 / 3.0
Works as Standalone Charger	N - Requires Host to function
Can be Bus Powered	N - External Power Required
POWER	
Input Voltage	9 ~ 24V DC
Idle Power Draw	13mA @ 12V Terminal Power
Max Power Draw	24W
Max Per Port Draw	1A (5W)
Supported Charge Protocols	CDP
ENVIRONMENTAL	
Operating Temperature	0C ~ 60C
Storage Temperature	-20C ~ 70C
Operating Humidity	15 ~ 85% RH
OS SUPPORT	
Supported Operating Systems	OS independent - No software or drivers required
WARRANTY	
Warranty Period	1 Year
PRODUCT URL	
Mfg Page	https://www.gearmo.com/shop/usb-3-4-port-rugged-industrial-din-rail-mount-hub-power-adapter/