

Technical Data Sheet Rev 06-240802

4-Port USB 3.0 Rugged Industrial DIN Rail & Surface Mount Hub

Model Number: GM-HU34



Features

- Compliant with USB 3.0 Standards
- Adds 4 additional USB High Speed ports
- Supplies independent over-current detection and circuit protection to all ports
- Includes both DIN-Rail and mounting brackets for multiple mounting options
- Constructed with an Industrial designed rugged metal chassis

Package Contents

- 3-Pin Terminal Block
- DIN rail bracket
- Hub
- Mounting Bracket
- Screw Pack
- USB Cable

Specifications

OVERVIEW

Model No	GM-HU34
Product Type	USB Hub
Compliance	None or N/A
UPC	736983901088
Country of Origin	China
LED indicators	None or N/A
Chipset	VL811-Q8P
Electrical Protections	15KV

PHYSICAL

Ship Weight (lbs)	0.5 lbs
Ship Weight (kg)	0.23 kg
Item Weight	0.5 lbs
Length	5.47 inches
Width	2.69 inches
Height	0.98 inches
Material	Steel
Color	Black
Mountable	Din-Rail Surface Mount

Specifications Cont.

CONNECTIONS	
USB Specification	USB 3.2 Gen 1
Upstream Port Type	USB 3.2G1 / 3.0 Type-B Female
Maximum Data Rate	5 Gbps
Downstream Port Count	4
Downstream Port Type	4x Type A USB 3.2 G1 / 3.0
Works as Standalone Charger	N - Requires Host to function
Can be Bus Powered	N - External Power Required
POWER	
Input Voltage	9 ~ 24V DC
Idle Power Draw	13mA @ 12V Terminal Power
Max Power Draw	24W
Max Per Port Draw	1A (5W)
Supported Charge Protocols	CDP
ENVIRONMENTAL	
Operating Temperature	0C ~ 60C
Storage Temperature	-20C ~ 70C
Operating Humidity	15 ~ 85% RH
OS SUPPORT	
Supported Operating Systems	OS independent - No software or drivers required
WARRANTY	
Warranty Period	1 Year
PRODUCT URL	
Mfg Page	https://www.gearmo.com/shop/4-port-usb3-rugged-industrial-din-rail-mount-hub/