

Technical Data Sheet Rev 06-241203

4-Port USB 3.2 Gen 1 Industrial Metal Hub w/15KV ESD Protection

Model Number: GM-HU34DW-BRKT



Features

- Adds 4 USB 3.0 5Gbps Compliant Ports
- Power input surge protection to 600W for each port
- Easily Mounts to a DIN Rail or Flat Surface
- Rugged industrial-grade chassis for harsh environments
- NOTE: This product DOES NOT include a power supply. The version with a power supply is Model No. GM-HU34DW

Package Contents

- DIN rail bracket
- Hub
- Mounting Bracket
- USB Cable

Specifications

OVERVIEW

Model No	GM-HU34DW-BRKT
Product Type	USB Hub
Compliance	REACH RoHS
UPC	045079163850
Country of Origin	China
LED indicators	Port Status Power
Chipset	VL817-Q7S
Electrical Protections	15KV

PHYSICAL

Ship Weight (lbs)	1.12 lbs
Ship Weight (kg)	0.51 kg
Length	4.57 inches
Width	2.09 inches
Height	1.02 inches
Material	Steel
Color	Black
Mountable	Din-Rail Surface Mount

Specifications Cont.

CONNECTIONS

USB Specification	USB 3.2 Gen 1
Upstream Port Type	USB 3.2G1 / 3.0 Type-B Female
Maximum Data Rate	5 Gbps
Downstream Port Count	4
Downstream Port Type	4x Type A USB 3.2 G1 / 3.0
Works as Standalone Charger	N - Requires Host to function
Can be Bus Powered	N - External Power Required

POWER

Input Voltage	9 ~ 24V DC
Idle Power Draw	13 mA @12v DC
Max Power Draw	20W
Max Per Port Draw	1.5A (BC 1.2)
Supported Charge Protocols	Apple Charge 2.4A CDP DCP SDP

ENVIRONMENTAL

Operating Temperature	0C ~ 55C
Storage Temperature	-20C ~ 75C
Operating Humidity	5% to 95% RH

OS SUPPORT

Supported Operating Systems	OS independent - No software or drivers required
-----------------------------	--

WARRANTY

Warranty Period	1 Year
-----------------	--------

PRODUCT URL

Product Page	https://www.gearmo.com/shop/usb-3-2-gen1-4-port-industrial-metal-hub-w-15kv-esd-protection-copy/
--------------	---